

**Prüfbericht 366-0326-17-WIRD  
zur Erteilung der ECE (E1) 124R- 001359**

ANLAGE: 9.1

Hersteller: DEDICO TYRE CO., LTD NO. 30-5-5-1

Radtyp: DEDICO DDC39829

Stand: 10.08.2017



Seite: 1 von 2

**Manufacturer** : FIAT, OPEL / VAUXHALL**Wheel dates:**

Wheel size according to standard : 6 J X 16

Off set(mm) : 36,5

Hole circle (mm)/number of holes : 98/5

centering type : centering fixed

**Technical dates, short form**

| version         | Version name         |                          | Centering hole (mm) | Centering material | Permissible wheel Load (kg) | Permissible rolling Circumference (mm) | Valid from Production date |
|-----------------|----------------------|--------------------------|---------------------|--------------------|-----------------------------|--|----------------------------|
|                 | Wheel identification | Centering identification |                     |                    |                             |  |                            |
| DEDICO DDC39829 | DEDICO DDC39829      | Without                  | 58                  |                    | 745                         | 1950                                   | 24/17                      |
| MAMST36-6016    | MAMST36-6016         | Without                  | 58                  |                    | 745                         | 1950                                   | 24/17                      |
| WLM39829        | WLM39829             | Without                  | 58                  |                    | 745                         | 1950                                   | 24/17                      |
| XM 39829        | XM 39829             | Without                  | 58                  |                    | 745                         | 1950                                   | 24/17                      |

Prescribed systems in the vehicle must be functioning with the use of the described rim combination.

**Scope/Vehicle Manufacturer** : FIAT

Mounting parts : conical collar bolt M12x1,25, tapered thread 60 Grad, for Type : 263

Mounting parts : conical collar bolt M12x1,5, tapered thread 60 Grad, for Type : 199

Tightening torque for fixing parts : 90 Nm for Type : 263  
110 Nm for Type : 199commercial type: **FIAT DOBLO**

| Vehicle type | Approval           | kW      | Tires      | Restrictions of tires | Restrictions |
|--------------|--------------------|---------|------------|-----------------------|--------------|
| 263          | e3*2007/46*0002*.. | 55 - 99 | 195/60R16C |                       | 75); 1); 33) |
| 263          | e3*2007/46*0007*.. | 66 - 99 | 195/60R16C |                       | 1); 33)      |

commercial type: **FIAT PUNTO, PUNTO ABARTH, FIAT 500L**

| Vehicle type | Approval            | kW            | Tires  | Restrictions of tires | Restrictions  |
|--------------|---------------------|---------------|--|-----------------------|---|
| 199          | e3*2001/116*0217*.. | 59 - 88       | 205/55R16 91H                                    |                       | *) ; Fiat 500L Living; 1); 33)                        |
| 199          | e3*2001/116*0217*.. | 62 - 77       | 195/60R16<br>205/55R16 91H                       |                       | *) ; Fiat 500L; Hatchback; Front wheel drive; 1); 33) |
| 199          | e3*2001/116*0217*.. | 62 - 63<br>77 | 195/60R16<br>205/55R16<br>195/60R16<br>205/55R16 |                       | *) ; FIAT 500L only; 1); 33)                          |
| 199          | e3*2001/116*0217*.. | 62 - 88       | 205/55R16  |                       | *) ; Fiat 500L Trekking; 1); 33)                      |
| 199          | e3*2001/116*0217*.. | 62 - 88       | 205/55R16  |                       | *) ; FIAT 500L only; 1); 33)                          |

**Prüfbericht 366-0326-17-WIRD  
zur Erteilung der ECE (E1) 124R- 001359**

ANLAGE: 9.1

Hersteller: DEDICO TYRE CO., LTD NO. 30-5-5-1

Radtyp: DEDICO DDC39829

Stand: 10.08.2017



Seite: 2 von 2

commercial type: **FIAT PUNTO, PUNTO ABARTH, FIAT 500L**

| Vehicle type | Approval            | kW | Tires      | Restrictions of tires | Restrictions                          |
|--------------|---------------------|----|------------|-----------------------|---------------------------------------|
| 199          | e3*2001/116*0217*.. | 62 | 195/60R16C |                       | *); Fiat 500L<br>Trekking;<br>1); 33) |
|              |                     |    | 205/55R16  |                       |                                       |
|              |                     | 77 | 195/60R16C |                       |                                       |
|              |                     |    | 205/55R16  |                       |                                       |

Prescribed systems in the vehicle must be functioning with the use of the described rim combination.

**Scope/Vehicle Manufacturer** : OPEL / VAUXHALL

Mounting parts : conical collar bolt M12x1,25, tapered thread 60 Grad

Tightening torque for fixing parts : 90 Nm

commercial type: **COMBO**

| Vehicle type | Approval           | kW     | Tires      | Restrictions of tires | Restrictions |
|--------------|--------------------|--------|------------|-----------------------|--------------|
| Combo-D      | e3*2007/46*0079*.. | 66 -99 | 195/60R16C |                       | 1); 33)      |

commercial type: **COMBO VAN**

| Vehicle type | Approval           | kW     | Tires      | Restrictions of tires | Restrictions |
|--------------|--------------------|--------|------------|-----------------------|--------------|
| Combo-D-Van  | e3*2007/46*0076*.. | 55 -99 | 195/60R16C |                       | 75I; 1); 33) |

\*) The remarks under the listed restrictions/conditions are to be kept. If additional trademarks or sale- names are listed, so there are only this vehicles permissible. All other vehicles to this one application are not concerned.

### Restrictions

- 75I) The permitted axle load of the vehicle shall not exceed the double as on page 1 of this attachment mentioned wheel load under consideration of the mentioned rolling circumference, if necessary the increased axle load in trailer operation has to be adapted or to be cancelled
- 1) To be kept:
- the standard wheel size and offset.
  - tyre size with service description (load and speed index) and tyre brand commitments
  - as well as limitations to snow tyres (M+S) from the car documents.
  - requirements and limitations of snow chains from the operating licence and the operation manual.
- 33) The standard fixing parts and accessories of the vehicle manufacturer for the corresponding series-wheel must be used.