

**Prüfbericht 366-0470-17-WIRD
zur Erteilung der ECE (E1) 124R- 001376**

ANLAGE: 9.1

Hersteller: DEDICO TYRE CO., LTD NO. 30-5-5-1

Radtyp: DEDICO DDC35579

Stand: 15.11.2017



Seite: 1 von 2

Manufacturer : GM DAEWOO (ROK), OPEL, OPEL / VAUXHALL

Wheel dates:

Wheel size according to standard : 6 1/2 J X 16 Off set(mm) : 39

Hole circle (mm)/number of holes : 105/5 centering type : centering fixed

Technical dates, short form

version	Version name		Centering hole (mm)	Centering material	Permissible wheel Load (kg)	Permissible rolling Circumference (mm)	Valid from Production date
	Wheel identification	Centering identification					
DEDICO DDC35579	DEDICO DDC35579	Without	56,6		550	1935	05/15
MAMST12-6516	MAMST12-6516	Without	56,6		550	1935	05/15
WLM35579	WLM35579	Without	56,6		550	1935	05/15
XM 35579	XM 35579	Without	56,6		550	1935	05/15

Prescribed systems in the vehicle must be functioning with the use of the described rim combination.

Scope/Vehicle Manufacturer : GM DAEWOO (ROK)

Mounting parts : conical collar nut M12x1,5, tapered thread 60 Grad

Tightening torque for fixing parts : 140 Nm

commercial type: **CHEVROLET CRUZE**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
CHIR	e50*2007/46*0007*..	104	205/60R16 92V 215/60R16 95H		1); 2); 33)

Prescribed systems in the vehicle must be functioning with the use of the described rim combination.

Scope/Vehicle Manufacturer : OPEL, OPEL / VAUXHALL

Mounting parts : conical collar nut M12x1,5, tapered thread 60 Grad

Tightening torque for fixing parts : 125 Nm for Type : P-J; P-J/V
140 Nm for Type : P-J/SW; P-J/SW/V

commercial type: **AST/GTC, ZAFIRA, CASCADA, ZAFIRA TOURER, ASTRA NOTCHBACK**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
P-J/SW	e4*2007/46*0204*..	70 - 103	205/60R16 92H 215/60R16 95H		*) ; Only ASTRA SPORTS TOURER;
		74 - 103	205/55R16 91H		1); 2); 33)

commercial type: **ASTRA, ASTRA NOTCHBACK**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
P-J	e1*2007/46*0141*..	70 - 103	205/60R16 92H 215/60R16 95H		*) ; notchback; 1); 2); 33)
P-J	e1*2007/46*0141*..	64 - 103	205/55R16 91H 205/60R16 92H 215/60R16 95H		*) ; Hatchback; 1); 2); 33)

Prüfbericht 366-0470-17-WIRD
zur Erteilung der ECE (E1) 124R- 001376

ANLAGE: 9.1

Hersteller: DEDICO TYRE CO., LTD NO. 30-5-5-1

Radtyp: DEDICO DDC35579

Stand: 15.11.2017



Seite: 2 von 2

commercial type: **ASTRA SPORTS TOURER/ZAFIRA TOURER**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
P-J/SW/V	e4*2007/46*0308*..	85 - 103	205/60R16 215/60R16		*) ; Only ASTRA SPORTS TOURER; 1); 2); 33)

commercial type: **ASTRA VAN**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
P-J/V	e4*2007/46*0309*..	70	205/60R16 92H		1); 2); 33)
			215/60R16 95H		
		85	205/60R16		
			215/60R16		
		103	205/60R16		
			215/60R16		
P-J/V	e4*2007/46*0309*..	70	205/60R16 92H		1); 2); 33)
			215/60R16 95H		

*) The remarks under the listed restrictions/conditions are to be kept. If additional trademarks or sale- names are listed, so there are only this vehicles permissible. All other vehicles to this one application are not concerned.

Restrictions

- 1) To be kept:
 - the standard wheel size and offset.
 - tyre size with service description (load and speed index) and tyre brand commitments
 - as well as limitations to snow tyres (M+S) from the car documents.
 - requirements and limitations of snow chains from the operating licence and the operation manual.
- 2) Only permissible at vehicle models, which are allowed to use steel wheels as standard.
- 33) The standard fixing parts and accessories of the vehicle manufacturer for the corresponding series-wheel must be used.

R124 E1*124R00/01*1376*00