

**Prüfbericht 366-0294-17-WIRD
zur Erteilung der ECE (E1) 124R- 001324**

ANLAGE: 9.1

Hersteller: DEDICO TYRE CO., LTD NO. 30-5-5-1

Radtyp: DEDICO DDC32229

Stand: 20.07.2017



Seite: 1 von 2

Manufacturer : FORD**Wheel dates:**

Wheel size according to standard : 5 1/2 J X 14 H2 Off set(mm) : 37,5

Hole circle (mm)/number of holes : 108/4 centering type : centering fixed

Technical dates, short form

version	Version name		Centering hole (mm)	Centering material	Permissible wheel Load (kg)	Permissible rolling Circumference (mm)	Valid from Production date
	Wheel identification	Centering identification					
DEDICO DDC32229	DEDICO DDC32229	Without	63,3		435	1800	18/12
MAMST 15-5514	MAMST 15-5514	Without	63,3		435	1800	18/12
WLM 32229	WLM 32229	Without	63,3		435	1800	18/12
XM 32229	XM 32229	Without	63,3		435	1800	18/12

Prescribed systems in the vehicle must be functioning with the use of the described rim combination.

Scope/Vehicle Manufacturer : FORD

Mounting parts : conical collar nut M12x1,5, tapered thread 60 Grad, for Type : JR8

Accessories : Serie

Mounting parts : conical collar nut M12x1,5, tapered thread 60 Grad, for Type : KAF; (Kegelbund)

Mounting parts : conical collar nut M12x1,5, tapered thread 60 Grad, for Type : JN8; JA8-LPG; JA8

Tightening torque for fixing parts : 100 Nm for Type : JA8; JA8-LPG; JN8; JR8
120 Nm for Type : KAFcommercial type: **FIESTA**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
JA8	e9*2001/116*0069*..	44 - 103	175/65R14		1); 33)
JA8-LPG	e13*2007/46*1058*..	71	175/65R14 M+S 175/65R14 82		1); 33)
JR8	DE*2007/46*0072*..	50 - 66	175/65R14 82		1); 33)
JR8	e9*2007/46*0002*..	50 - 70	175/65R14 82		1); 33)

commercial type: **Ford KA, Ford KA+**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
KAF	e13*2007/46*1637*..	52 - 63	165/70R14 165/70R14 M+S		77E; 1); 33)

commercial type: **TRANSIT COURIER**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
JN8	e13*2007/46*1349*..	55	175/65R14 M+S		1); 33)
JN8	e13*2007/46*1349*..	55	175/65R14		1); 33)

Restrictions

- 77E) The indirect Tire Pressure Monitoring system must be calibrated. The instructions of the manual must be followed.
- 1) To be kept:
- the standard wheel size and offset.
 - tyre size with service description (load and speed index) and tyre brand commitments
 - as well as limitations to snow tyres (M+S) from the car documents.
 - requirements and limitations of snow chains from the operating licence and the operation manual.
- 33) The standard fixing parts and accessories of the vehicle manufacturer for the corresponding series-wheel must be used.