

**Prüfbericht 366-0301-17-WIRD
zur Erteilung der ECE (E1) 124R- 001326**

ANLAGE: 9.1

Hersteller: DEDICO TYRE CO., LTD NO. 30-5-5-1

Radtyp: DEDICO DDC33789

Stand: 25.07.2017



Seite: 1 von 2

Manufacturer : AUTOMOBILES DACIA S.A., RENAULT

Wheel dates:

Wheel size according to standard : 6 J X 15

Off set(mm) : 40

Hole circle (mm)/number of holes : 100/4

centering type : centering fixed

Technical dates, short form

version	Version name		Centering hole (mm)	Centering material	Permissible wheel Load (kg)	Permissible rolling Circumference (mm)	Valid from Production date
	Wheel identification	Centering identification					
DEDICO DDC33789	DEDICO DDC33789	Without	60		560	1895	01/15
DEDICO DDC33789	DEDICO DDC33789	Without	60		580	1850	01/15
MAMST20-6015	MAMST20-6015	Without	60		580	1850	01/15
WLM33789	WLM33789	Without	60		580	1850	01/15
XM 33789	XM 33789	Without	60		580	1850	01/15

Prescribed systems in the vehicle must be functioning with the use of the described rim combination.

Scope/Vehicle Manufacturer : AUTOMOBILES DACIA S.A.

Mounting parts : conical collar bolt M12x1,5, tapered thread 60 Grad

Tightening torque for fixing parts : 105 Nm

commercial type: **LOGAN,SANDERO,DUSTER,LODGY,DOKKER**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
SD	e2*2001/116*0314*..	55 -66	185/65R15 88		*) ; Logan (notchback); ; Sandero (hatchback); ; 1); 33)
SD	e2*2001/116*0314*..	55 -66	185/65R15 88		*) ; Logan MCV; ; 1); 33)
SD	e2*2001/116*0314*..	54 -66	185/65HR15		*) ; ; Only Logan II; only Sandero II; not MCV II; 1); 33)
SD	e2*2007/46*0030*..	54 -66	185/65R15		*) ; ; only Logan II; only Sandero II; not MCV II; 1); 33)

Prescribed systems in the vehicle must be functioning with the use of the described rim combination.

Scope/Vehicle Manufacturer : RENAULT

Mounting parts : conical collar bolt M12x1,5, tapered thread 60 Grad

Tightening torque for fixing parts : 105 Nm for Type : AG

110 Nm for Type : R

Prüfbericht 366-0301-17-WIRD
zur Erteilung der ECE (E1) 124R- 001326

ANLAGE: 9.1

Hersteller: DEDICO TYRE CO., LTD NO. 30-5-5-1

Radtyp: DEDICO DDC33789
Stand: 25.07.2017

Seite: 2 von 2

commercial type: **CLIO, CAPTUR**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
R	e2*2001/116*0327*..	48	185/65R15		*); Clio 4 from Mj. 2012; 54kW from NG*48, 66kW from NG*46; 48 kW from e2*2001/116*0327*61; 55kW from e2*2001/116*0327*46; not Variante "5RTL and 5RVL"; not Captur; 1); 33)
		54 -66	185/65R15 M+S		
			185/65R15 88		
R	e2*2001/116*0327*..	48 -66	185/65R15		*); Grandtour; from NT*50; not Variante "7RTL and 7RVL"; 1); 33)

commercial type: **ZOE**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
AG	e2*2007/46*0251*..	43	185/65R15 88		1); 33)

*) The remarks under the listed restrictions/conditions are to be kept. If additional trademarks or sale- names are listed, so there are only this vehicles permissible. All other vehicles to this one application are not concerned.

Restrictions

- 1) To be kept:
 - the standard wheel size and offset.
 - tyre size with service description (load and speed index) and tyre brand commitments
 - as well as limitations to snow tyres (M+S) from the car documents.
 - requirements and limitations of snow chains from the operating licence and the operation manual.
- 33) The standard fixing parts and accessories of the vehicle manufacturer for the corresponding series-wheel must be used.