

**Prüfbericht 366-0293-17-WIRD
zur Erteilung der ECE (E1) 124R- 001333**

ANLAGE: 9.1

Hersteller: DEDICO TYRE CO., LTD NO. 30-5-5-1

Radtyp: DEDICO DDC33919

Stand: 20.07.2017



Seite: 1 von 3

Manufacturer : SEAT, SKODA, VOLKSWAGEN

Wheel dates:

Wheel size according to standard : 6 J X 15 H2 Off set(mm) : 38

Hole circle (mm)/number of holes : 100/5 centering type : centering fixed

Technical dates, short form

version	Version name		Centering hole (mm)	Centering material	Permissible wheel Load (kg)	Permissible rolling Circumference (mm)	Valid from Production date
	Wheel identification	Centering identification					
DEDICO DDC33919	DEDICO DDC33919	Without	57		520	1850	05/15
MAMST21-6015	MAMST21-6015	Without	57		520	1850	05/15
WLM 33919	WLM 33919	Without	57		520	1850	05/15
XM 33919	XM 33919	Without	57		520	1850	05/15

Prescribed systems in the vehicle must be functioning with the use of the described rim combination.

Scope/Vehicle Manufacturer : SEAT

Mounting parts : spherical collar bolt M14x1,5, diameter 26 mm

Tightening torque for fixing parts : 120 Nm

commercial type: **IBIZA**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
6J	e9*2001/116*0067*..	44 - 110	185/60R15		77E; 1); 33)
			185/60R15 M+S		
			59 175/65R15		
			66 175/65R15		
			77 175/65R15		
6J	e9*2001/116*0067*..	132	185/60R15 88		77E; 1); 33)
			185/60R15 88 M+S		
6J	e9*2001/116*0067*..	44 - 51	185/60R15		77E; 1); 33)
			66 - 110 185/60R15		
			77 175/65R15		
			103 175/65R15		
6JN	e9*2007/46*0001*..	44 - 63	185/60R15 84		1); 33)
			44 - 77 185/60R15 84 M+S		
			59 175/65R15 84		
			66 - 77 175/65R15 84H		
			185/60R15 84H		
6JN	e9*2007/46*0001*..	44 - 77	185/60R15 84		1); 33)
			77 175/65R15 84		

commercial type: **SEAT TOLEDO/LEON**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
1M	e9*97/27*0026*..	55 - 92	195/65R15		1); 33)
1M	e9*98/14*0026*..	50 - 110	195/65R15		1); 33)

**Prüfbericht 366-0293-17-WIRD
zur Erteilung der ECE (E1) 124R- 001333**

ANLAGE: 9.1

Hersteller: DEDICO TYRE CO., LTD NO. 30-5-5-1

Radtyp: DEDICO DDC33919

Stand: 20.07.2017



Seite: 2 von 3

commercial type: **TOLEDO**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
NH	e11*2007/46*0251*..	55 -92	185/60R15		*); from e11*2007/46*0251*01; Limousine; Front wheel drive; 1); 33)
		66 -92	195/55R15		

Prescribed systems in the vehicle must be functioning with the use of the described rim combination.

Scope/Vehicle Manufacturer : SKODA

Mounting parts : spherical collar bolt M14x1,5, diameter 26 mm

Tightening torque for fixing parts : 120 Nm

commercial type: **PRAKTIK**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
5J	N083	51 -63	185/55R15 M+S		1); 33)
			195/55R15		

commercial type: **RAPID**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
NH	e11*2007/46*0250*..	66	195/55R15		*); from e11*2007/46*0250*01; Front wheel drive; 1); 33)
		77	195/55R15		
		90	195/55R15		
NH	e11*2007/46*0250*..	55 -92	185/60R15		*); RAPID SPACEBACK; from NT*06; Front wheel drive; 1); 33)
NH	e11*2007/46*0250*..	55 -92	185/60R15		*); from e11*2007/46*0250*01; Limousine; Front wheel drive; 1); 33)

commercial type: **ROOMSTER, FABIA, PRAKTIK**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
5J	e11*2001/116*0291*..	44 -81	185/60R15		*); only Fabia; from e11*2001/116*0291*43; 1); 33)
5J	e11*2007/46*0013*..	44 -81	185/60R15		*); only Fabia; from e11*2007/46*0013*20; 1); 33)
5J	e11*2007/46*0013*..	77	195/55R15 85H		*); Fabia station wagon; 1); 33)

Prescribed systems in the vehicle must be functioning with the use of the described rim combination.

Prüfbericht 366-0293-17-WIRD
zur Erteilung der ECE (E1) 124R- 001333

ANLAGE: 9.1

Hersteller: DEDICO TYRE CO., LTD NO. 30-5-5-1

Radtyp: DEDICO DDC33919

Stand: 20.07.2017



Seite: 3 von 3

Scope/Vehicle Manufacturer : VOLKSWAGEN

Mounting parts : spherical collar bolt M14x1,5, diameter 26 mm

Tightening torque for fixing parts : 120 Nm

commercial type: **POLO**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
6R	e1*2001/116*0510*..	132	185/60R15 M+S		*) ; POLO; up to e1*2001/116*0510*15; 1); 33); VG8
6R	e1*2001/116*0510*..	44 - 103	185/60R15		*) ; POLO; 1); 33); VG8
		77 - 103	175/65R15		
		110	185/60R15 M+S		
6R	e1*2001/116*0510*..	44 - 77	185/60R15		*) ; Only CrossPolo; 1); 33); VG8
6R	e1*2007/46*0486*..	44 - 81	185/60R15		*) ; POLO; 1); 33); VG8
		110	185/60R15 M+S		

*) The remarks under the listed restrictions/conditions are to be kept. If additional trademarks or sale- names are listed, so there are only this vehicles permissible. All other vehicles to this one application are not concerned.

Restrictions

77E) The indirect Tire Pressure Monitoring system must be calibrated. The instructions of the manual must be followed.

1) To be kept:

- the standard wheel size and offset.
- tyre size with service description (load and speed index) and tyre brand commitments
- as well as limitations to snow tyres (M+S) from the car documents.
- requirements and limitations of snow chains from the operating licence and the operation manual.

33) The standard fixing parts and accessories of the vehicle manufacturer for the corresponding series-wheel must be used.

VG8) The use of the these wheels is not permitted on vehicle versions with brake disc diameters greater than 288 mm on the front axle.