

**Prüfbericht 366-0362-17-WIRD
zur Erteilung der ECE (E1) 124R- 001331**

ANLAGE: 9.1

Hersteller: DEDICO TYRE CO., LTD NO. 30-5-5-1

Radtyp: DEDICO DDC31709

Stand: 30.08.2017



Seite: 1 von 2

Manufacturer : SEAT, SKODA, VOLKSWAGEN

Wheel dates:

Wheel size according to standard : 5 J X 14

Off set(mm) : 35

Hole circle (mm)/number of holes : 100/4

centering type : centering fixed

Technical dates, short form

version	Version name		Centering hole (mm)	Centering material	Permissible wheel Load (kg)	Permissible rolling Circumference (mm)	Valid from Production date
	Wheel identification	Centering identification					
DEDICO DDC31709	DEDICO DDC31709	Without	57		435	1795	04/15
MAMST22-5014	MAMST22-5014	Without	57		435	1795	04/15
WLM31709	WLM31709	Without	57		435	1795	04/15
XM 31709	XM 31709	Without	57		435	1795	04/15

Prescribed systems in the vehicle must be functioning with the use of the described rim combination.

Scope/Vehicle Manufacturer : SEAT

Mounting parts : spherical collar bolt M12x1,5, diameter 26 mm

Tightening torque for fixing parts : 110 Nm

commercial type: **MII**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
AA	e13*2007/46*1168*..	44 -55	165/70R14 81		1); 33)
			175/65R14 82		
AAN	e13*2007/46*1183*..	55	165/70R14 81		1); 33)
			175/65R14 82		
AAN	e13*2007/46*1183*..	44 -55	165/70R14 81		1); 33)
			175/65R14 82		

Prescribed systems in the vehicle must be functioning with the use of the described rim combination.

Scope/Vehicle Manufacturer : SKODA

Mounting parts : spherical collar bolt M12x1,5, diameter 26 mm

Tightening torque for fixing parts : 110 Nm

commercial type: **CITIGO**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
AA	e13*2007/46*1169*..	44 -55	165/70R14 81		1); 33)
			175/65R14 82		
AAN	e13*2007/46*1184*..	44 -55	165/70R14 81		1); 33)
			175/65R14 82		

Prescribed systems in the vehicle must be functioning with the use of the described rim combination.

Scope/Vehicle Manufacturer : VOLKSWAGEN

Mounting parts : spherical collar bolt M12x1,5, diameter 26 mm

Tightening torque for fixing parts : 110 Nm

Prüfbericht 366-0362-17-WIRD
zur Erteilung der ECE (E1) 124R- 001331

ANLAGE: 9.1

Hersteller: DEDICO TYRE CO., LTD NO. 30-5-5-1

Radtyp: DEDICO DDC31709

Stand: 30.08.2017



Seite: 2 von 2

commercial type: **UP!**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
AA	e13*2007/46*1167*..	44 -55	165/70R14		1); 33)
			175/65R14		
		66	165/70R14		
			175/65R14		
AA	e13*2007/46*1167*..	60	165/70R14 M+S		*) ; e-up! ; 1); 33)
AA	e13*2007/46*1167*..	55	165/70R14		*) ; ; 1); 33)
			175/65R14		
AAN	e13*2007/46*1182*..	60	165/70R14 M+S		*) ; e-up! ; 1); 33)
AAN	e13*2007/46*1182*..	44 -55	165/70R14		1); 33)
			175/65R14		

*) The remarks under the listed restrictions/conditions are to be kept. If additional trademarks or sale- names are listed, so there are only this vehicles permissible. All other vehicles to this one application are not concerned.

Restrictions

- 1) To be kept:
 - the standard wheel size and offset.
 - tyre size with service description (load and speed index) and tyre brand commitments
 - as well as limitations to snow tyres (M+S) from the car documents.
 - requirements and limitations of snow chains from the operating licence and the operation manual.
- 33) The standard fixing parts and accessories of the vehicle manufacturer for the corresponding series-wheel must be used.

R124 001331