

**Prüfbericht 366-0287-17-WIRD  
zur Erteilung der ECE (E1) 124R- 001327**

ANLAGE: 9.1

Hersteller: DEDICO TYRE CO., LTD NO. 30-5-5-1

Radtyp: DEDICO DDC36069

Stand: 20.07.2017



Seite: 1 von 2

**Manufacturer : AUDI, SEAT, SKODA, VOLKSWAGEN**

**Wheel dates:**

Wheel size according to standard : 6 1/2 J X 16 Off set(mm) : 46

Hole circle (mm)/number of holes : 112/5 centering type : centering fixed

**Technical dates, short form**

version	Version name		Centering hole (mm)	Centering material	Permissible wheel Load (kg)	Permissible rolling Circumference (mm)	Valid from Production date
	Wheel identification	Centering identification					
DEDICO DDC36069	DEDICO DDC36069	Without	57		640	1930	07/17
MAMST29-6516	MAMST29-6516	Without	57		640	1930	07/17
WLM 36069	WLM 36069	Without	57		640	1930	07/17
XM 36069	XM 36069	Without	57		640	1930	07/17

Prescribed systems in the vehicle must be functioning with the use of the described rim combination.

**Scope/Vehicle Manufacturer : AUDI**

Mounting parts : spherical collar bolt M14x1,5, diameter 26 mm

Tightening torque for fixing parts : 120 Nm

commercial type: **AUDI A3, S3**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
8V	e1*2007/46*0607*..	77 - 140	205/55R16 205/55R16 M+S		*) ; not S3 ; ; not Limousine; 1); 33)

Prescribed systems in the vehicle must be functioning with the use of the described rim combination.

**Scope/Vehicle Manufacturer : SEAT**

Mounting parts : spherical collar bolt M14x1,5, diameter 26 mm

Tightening torque for fixing parts : 120 Nm

commercial type: **LEON / LEON SC / LEON ST / LEON X-PERIENCE**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
5F	e9*2007/46*0094*..	63 - 135	205/55R16		*) ; from e9*2007/46*0094*01; All-wheel drive; Front wheel drive; 1); 33)

Prescribed systems in the vehicle must be functioning with the use of the described rim combination.

**Scope/Vehicle Manufacturer : SKODA**

Mounting parts : spherical collar bolt M14x1,5, diameter 26 mm

Tightening torque for fixing parts : 120 Nm

**Prüfbericht 366-0287-17-WIRD**  
**zur Erteilung der ECE (E1) 124R- 001327**

ANLAGE: 9.1

Hersteller: DEDICO TYRE CO., LTD NO. 30-5-5-1

Radtyp: DEDICO DDC36069

Stand: 20.07.2017



Seite: 2 von 2

commercial type: **SKODA OCTAVIA**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
5E	e11*2007/46*0243*..	63	205/55R16		77E; 1); 33)
		66 - 81	205/55R16		
		103 - 135	205/55R16		

Prescribed systems in the vehicle must be functioning with the use of the described rim combination.

**Scope/Vehicle Manufacturer : VOLKSWAGEN**

Mounting parts : spherical collar bolt M14x1,5, diameter 26 mm

Tightening torque for fixing parts : 120 Nm

commercial type: **GOLF, GOLF VARIANT, GOLF SPORTSVAN**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
1 KM	e1*2007/46*0492*..	66 - 110	205/55R16		*) ; Golf 7 Variant; Golf 7 (Variant) only; 1); 33)
1K	e1*2007/46*0490*..	66 - 110	205/55R16		*) ; ; ; 1); 33)

commercial type: **GOLF, GOLF VARIANT, GOLF SPORTSVAN, E-GOLF**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
AU	e1*2007/46*0623*..	63 - 162	205/55R16		*) ; only Golf 7; 1); 33)
		162	205/55R16 M+S		

commercial type: **GOLF, GOLF VARIANT, GOLF SPORTSVAN, GOLF ALLTRACK**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
AUV	e1*2007/46*0627*..	63 - 110	205/55R16		*) ; Golf 7 Variant; only GOLF SPORTSVAN; 1); 33)

\*) The remarks under the listed restrictions/conditions are to be kept. If additional trademarks or sale- names are listed, so there are only this vehicles permissible. All other vehicles to this one application are not concerned.

**Restrictions**

77E) The indirect Tire Pressure Monitoring system must be calibrated. The instructions of the manual must be followed.

- 1) To be kept:
- the standard wheel size and offset.
  - tyre size with service description (load and speed index) and tyre brand commitments
  - as well as limitations to snow tyres (M+S) from the car documents.
  - requirements and limitations of snow chains from the operating licence and the operation manual.
- 33) The standard fixing parts and accessories of the vehicle manufacturer for the corresponding series-wheel must be used.