

**Prüfbericht 366-0307-17-WIRD
zur Erteilung der ECE (E1) 124R- 001325**

ANLAGE: 9.1

Hersteller: DEDICO TYRE CO., LTD NO. 30-5-5-1

Radtyp: DEDICO DDC32369

Stand: 27.07.2017



Seite: 1 von 3

Manufacturer : FIAT, FORD**Wheel dates:**

Wheel size according to standard : 5 1/2 J X 14 H2 Off set(mm) : 35

Hole circle (mm)/number of holes : 98/4 centering type :

Technical dates, short form

version	Version name		Centering hole (mm)	Centering material	Permissible wheel Load (kg)	Permissible rolling Circumference (mm)	Valid from Production date
	Wheel identification	Centering identification					
DEDICO DDC32369	DEDICO DDC32369	Without	58		463	1818	22/16
DEDICO DDC32369	DEDICO DDC32369	Without	58		470	1790	22/16
MAMST37-5514	MAMST37-5514	Without	58		470	1790	22/16
WLM32369	WLM32369	Without	58		470	1790	22/16
XM 32369	XM 32369	Without	58		470	1790	22/16

Prescribed systems in the vehicle must be functioning with the use of the described rim combination.

Scope/Vehicle Manufacturer : FIAT

Mounting parts : conical collar bolt M12x1,25, tapered thread 60 Grad

Tightening torque for fixing parts : 90 Nm for Type : 188
100 Nm for Type : 169; 312commercial type: **FIAT PANDA**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
169	e3*2001/116*0151*..	51 -55	185/65R14		*) ; Only FIAT Panda 4x4 Cross; 1); 33)
169	e3*2001/116*0151*..	44 -57	175/65R14		*) ; Only FIAT Panda 4x4 Cross; Only FIAT Panda 4x4; 1); 33)
		51 -55	185/65R14 M+S		
169	e3*2001/116*0151*..	44 -57	165/70R14		*) ; Not FIAT Panda 4x4 Cross; Only Benzin-/Methan-Motor; Front wheel drive; 1); 33)
			175/65R14		
169	e3*2001/116*0151*..	44 -55	185/65R14		*) ; Only FIAT Panda 4x4 Cross; 1); 33)

**Prüfbericht 366-0307-17-WIRD
zur Erteilung der ECE (E1) 124R- 001325**

ANLAGE: 9.1

Hersteller: DEDICO TYRE CO., LTD NO. 30-5-5-1

Radtyp: DEDICO DDC32369

Stand: 27.07.2017



Seite: 2 von 3

commercial type: **FIAT PANDA**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
169	e3*2001/116*0151*..	38 -57	165/70R14 M+S	Only Benzin-/Methan-Motor; Front wheel drive	*); All-wheel drive; Front wheel drive; 1); 33)
			175/65R14 82	Only Benzin-/Methan-Motor; Front wheel drive	
		44 -55	165/70R14	Only FIAT Panda 4x4; All-wheel drive	
			185/65R14 M+S	All-wheel drive	
169	e3*2001/116*0151*..	57	165/70R14		*); Only Benzin- /Methan-Motor; Front wheel drive; 1); 33)
			175/65R14 82		
169	e3*2001/116*0151*..	44 -55	165/70R14		*); Not FIAT Panda 4x4 Cross; Only FIAT Panda 4x4; 1); 33)
			185/65R14		

commercial type: **FIAT PUNTO**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
188	e3*98/14*0048*..	44 -59	165/70R14-81Q M+S		1); 33)
			44 -63	185/60R14-82Q M+S	
		44 -70	165/70R14 81		
			185/60R14-82H		

commercial type: **FIAT 500 / ABARTH, YPSILON, PANDA**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
312	e3*2007/46*0064*..	51	165/65R14		*); Fiat 500; Not for Fiat 500 C (Cabrio); 1); 33)
312	e3*2007/46*0064*..	44 -77	175/65R14		*); Fiat 500; 1); 33)
312	e3*2007/46*0064*..	44 -70	175/65R14		*); Only Fiat Panda (station wagon); 1); 33)
			51 -55	165/65R14	
		165/70R14			
312	e3*2007/46*0064*..	44 -70	175/65R14		*); Fiat 500; Panda; 1); 33)
			51 -55	165/65R14	
		165/70R14			
312	e3*2007/46*0064*..	51	165/65R14		*); Fiat 500; 1); 33)
			175/65R14-82T		
		55 -70	175/65R14		
		74	175/65R14-82H		

commercial type: **FIAT 500 / 500 ABARTH**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
312	e3*2001/116*0261*..	51	165/65R14		*); Fiat 500; Fiat 500 C (Cabrio); 1); 33)
		51 -74	175/65R14		

Prüfbericht 366-0307-17-WIRD
zur Erteilung der ECE (E1) 124R- 001325

ANLAGE: 9.1

Hersteller: DEDICO TYRE CO., LTD NO. 30-5-5-1

Radtyp: DEDICO DDC32369

Stand: 27.07.2017



Seite: 3 von 3

commercial type: **FIAT 500 / 500 ABARTH**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
312	e3*2001/116*0261*..	51	165/65R14 79		1); 33)
		51 -70	175/65R14 82		
		73 -74	175/65R14-82H		

Prescribed systems in the vehicle must be functioning with the use of the described rim combination.

Scope/Vehicle Manufacturer : **FORD**

Mounting parts : conical collar bolt M12x1,25, tapered thread 60 Grad

Tightening torque for fixing parts : 100 Nm

commercial type: **KA**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
RU8	e3*2001/116*0280*..	51 -55	165/65R14 M+S		1); 33)
			165/65R14 83		
			175/65R14 M+S		
			175/65R14 82		

*) The remarks under the listed restrictions/conditions are to be kept. If additional trademarks or sale- names are listed, so there are only this vehicles permissible. All other vehicles to this one application are not concerned.

Restrictions

- 1) To be kept:
 - the standard wheel size and offset.
 - tyre size with service description (load and speed index) and tyre brand commitments
 - as well as limitations to snow tyres (M+S) from the car documents.
 - requirements and limitations of snow chains from the operating licence and the operation manual.
- 33) The standard fixing parts and accessories of the vehicle manufacturer for the corresponding series-wheel must be used.