

**Prüfbericht 366-0504-17-WIRD**  
**zur Erteilung der ECE (E1) 124R- 001375**

ANLAGE: 9.1

Hersteller: DEDICO TYRE CO., LTD NO. 30-5-5-1

Radtyp: DEDICO DDC3555

Stand: 06.12.2017



Seite: 1 von 3

**Manufacturer : VOLKSWAGEN****Wheel dates:**

Wheel size according to standard : 16 x 6,5J

Off set(mm) : 51

Hole circle (mm)/number of holes : 120/5

centering type : centering fixed

**Technical dates, short form**

version	Version name		Centering hole (mm)	Centering material	Permissible wheel Load (kg)	Permissible rolling Circumference (mm)	Valid from Production date
	Wheel identification	Centering identification					
DEDICO DDC3555	DEDICO DDC3555	Without	65		900	2100	28/14
MAMST7-6516	MAMST7-6516	Without	65		900	2100	28/14
WLM 3555	WLM 3555	Without	65		900	2100	28/14
XM 3555	XM 3555	Without	65		900	2100	28/14

Prescribed systems in the vehicle must be functioning with the use of the described rim combination.

**Scope/Vehicle Manufacturer : VOLKSWAGEN**

Mounting parts : spherical collar bolt M14x1,5, diameter 28 mm

Tightening torque for fixing parts : 180 Nm

commercial type: **CALIFORNIA**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
7HMA	e1*2001/116*0289*..	75 - 110	205/65R16C 215/65R16C		*) ; from e1*2001/116*0289*25; T6; 1); 36)

commercial type: **CALIFORNIA, KOMBI, MULTIVAN, CALIFORNIA BEACH**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
7HC	e1*2001/116*0220*..	62 - 110	205/65R16C 215/65R16C 215/65R16C M+S		*) ; T6; Station wagon; Van; 1); 36)

commercial type: **TRANSPORTER**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
7J0	e1*2007/46*0130*..	62 - 75 62 - 110 75	215/65R16C 205/65R16C 215/65R16C M+S		*) ; from e1*2007/46*0130*16; T6; All-wheel drive; Front wheel drive; 1); 36)
7J0	e1*2007/46*0130*..	62 - 150	205/65R16 103 215/65R16 102		*) ; Lkw box van (series); 1); 36)

**Prüfbericht 366-0504-17-WIRD  
zur Erteilung der ECE (E1) 124R- 001375**

ANLAGE: 9.1

Hersteller: DEDICO TYRE CO., LTD NO. 30-5-5-1

Radtyp: DEDICO DDC3555

Stand: 06.12.2017



Seite: 2 von 3

commercial type: **TRANSPORTER**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
7J0	e1*2007/46*0130*..	62 - 103	205/65R16C 103		*); Lkw box van (series); pickup truck (series); Lorry body with cab; All-wheel drive; Front wheel drive; 1); 36)
			215/65R16C 102/100		
7J0	L225	62 - 128	205/65R16C 103T		*); pickup truck (series); Lorry body with cab; short wheel base; long wheel base; All-wheel drive; Front wheel drive; 1); 36)
			215/65R16C 109		

commercial type: **TRANSPORTER, CALIFORNIA, MULTIVAN**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
7HC	e1*2001/116*0220*..	62 - 128	205/65R16C		*); T5; up to e1*2001/116*0220*35; 1); 36)
			215/65R16C		
7HCA	e1*2001/116*0286*..	96 - 128	205/65R16C 103		1); 36)
			215/65R16C 102/100		
			215/65R16C 106/104		
7HK	L148	63 - 128	205/65R16C		1); 36)
			215/65R16C 109		
7HKX0	L148	63 - 128	205/65R16C 103T		1); 36)
			215/65R16C 109		
7HM	e1*2001/116*0218*..	62 - 128	205/65R16C 103T		1); 36)
			215/65R16C 109		
7HMA	e1*2001/116*0289*..	62 - 103	205/65R16C 103T		1); 36)
		62 - 128	215/65R16C 102/100		

\*) The remarks under the listed restrictions/conditions are to be kept. If additional trademarks or sale- names are listed, so there are only this vehicles permissible. All other vehicles to this one application are not concerned.

**Restrictions**

- 1) To be kept:
  - the standard wheel size and offset.
  - tyre size with service description (load and speed index) and tyre brand commitments
  - as well as limitations to snow tyres (M+S) from the car documents.
  - requirements and limitations of snow chains from the operating licence and the operation manual.

**Prüfbericht 366-0504-17-WIRD  
zur Erteilung der ECE (E1) 124R- 001375**

**ANLAGE: 9.1**

Hersteller: DEDICO TYRE CO., LTD NO. 30-5-5-1

Anlage 9 - Verwendungsbereich



Radtyp: DEDICO DDC3555

Stand: 06.12.2017

Seite: 3 von 3

36) The standard fixing parts for the standard steel wheel of this vehicle type shall be used.

R124 E1\*124R00/01\*1375\*00, Korr. 01